

0000

SINLOON

®

0000/000

LED Floodlight

Power: 600W/750W

Applications



It is suitable for using in parks, hotels, bars, gardens, buildings, lamp posts, playing grounds, stadiums.



[Data Spec. 600W 750W](#)

Technical Information	Model No.	Unit	TSC600CW-SC	TSC750CW-SC
-----------------------	-----------	------	-------------	-------------

Wattage	[W]	600W±5%	750W±5%
Input Voltage	[V]	AC90-305V	AC90-305V
Power Factor	[pF]	≥0.95	≥0.95
Op. Frequency	[Hz]	50/60Hz	50/60Hz
Luminous Flux	[lm]	≥66000lm	≥82500LM
Efficiency	[lm/W]	>110	>110
CRI	[Ra]	>70	>70
CCT	[K]	2700-7000K	2700-7000K
LED Driver(brand)		MOSO DRIVER	MOSO DRIVER
Output Voltage	[V]	20-54V	20-54V
Output Current	[mA]	4200mA±3%	4200mA±3%*2
Kind of LED	[SMD]	8 x COB	10 x COB
Brand of LED Chip		SAN'AN	SAN'AN
Beam Angle		30°/60°/120°	30°/60°/120°
Average Life	[hrs]	50000	50000
Maintenance Luminous Flux 70%	[hrs]	50000	50000
Ta - Working Ambinet Temp.	[°C]	-40□ to +60□	-40□ to +60□
Tc - Working Temperature	[°C]	+90□	+90□
IP - Index Protection	IP	IP65	IP65

LED Floodlight - TCS600W TSC750W

0000 00, 09 00 2017 06:49

Reflector Material	-	-
Difusor Material	PC	PC
Body Material	stretching Alu.	stretching Alu.
Weight	[Kg] 15.4kgs	17.8kgs

Dimensions of Product (L x W x H) [mm]	490*475*128 mm	490*598*128 mm
--	----------------	----------------

Certificates	RoHS/CE	RoHS/CE
Warranty by Supplier	2 Years	2 Years

Inner	Kind of Packing	white box	white box
-------	-----------------	-----------	-----------

Barcode	-	-
Dimension (L x W xH)	[mm]	520*520*220 mm 520*620*220 mm

Pcs/Ctn	Un/Cx	1pc/Cx	1pc/Cx
---------	-------	--------	--------

Outer	Kind of Packing	Export carton Packing	Export carton Packing
-------	-----------------	-----------------------	-----------------------

Barcode	-	-	
Weight	[kg]	16.4kgs	19kgs
Dimension (L x W x H)	[mm]	520*520*220 mm	520*620*220 mm
Pcs/Ctn	Un/Cx	1pc/Ctn	1pc/Ctn

XX.