

SINLOON®

LED 投光燈/泛光燈系列

光束精準反射效果最佳

LED Flood Light

Good heat dissipation performance

Model No. MLL-TGD80W

□ Features:

- Power Range: 10W ~ 200Watt.
- High utilization of power, PF>0.9 .
- IP Rating is up to IP65
- Lifespan 50,000 hours
- Good heat dissipation performance
- Metallic aluminum PCB with excellent heat conduction and cooling.
- Compared with traditional ones, Energy-saving percentage 60%.
- Aluminum die-cast alloy body and toughened glass, durable and completely corrosion resistance.

□ Application

LED Flood Light widely application for
Dancing halls, Modern buildings,
Advertising boards, External walls,
Squares, Streets, Parks, Scenic spot,
Karts caves, Garden lighting projects and ect.



Characteristic Parameters:

型號 Model No. MLL Series:	MLL-TGD80B
尺寸 Dimension (L*W*T): mm	360*288*110
功率 Power:	80W
輸入電壓 Input Voltage:	AC100-240V 50/60Hz
類型 LED Type:	Cree, Epistar , Bridge and Others COB
功率/亮度 System Power (W):	80-100lm/W
光通亮 LED Flux (lm):	6400lm±10%
燈具效率 Lighting Factor:	>87%
功率系數 Power Factor:	≥0.9 PF
色溫 Color Temperature (K)	Warm, White, 2700K-7000K
顯色指數 Color Rendering Index (CRI):	Ra ≥70
發光角度 Illumination Angle:	120°
壽命 Lifespan:	50,000hrs
環境溫度 Ambient Temperature (°C):	25°C
應用環境 Temperature Operating:	-20 ~ +40°C
認證 Certificate:	CE,SAA,ETL,DLC.
保固 Warranty:	3 Years

* 圖片已近似實物, 最終產品以實物外型為準.

* If you have any question which is not in the specification, please contact us.

* 在本規格書裡如果您未能找或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡.

