

SINLOON®

聚光射燈/泛光燈

LED Floodlight

Power:

15W

20W

TSC series

## ■ Applications

It is suitable for using in parks, hotels, bars, gardens, buildings, lamp posts, playing grounds, stadiums.



■ Specification		Model:	TSC15CW-SD16	TSC20W-SD
Technical Information	Wattage	[W]	15W	20W
	Input Voltage	[V]	AC90-265V	AC90-265V
	Power Factor		≥0.95	≥0.95
	Op. Frequency	[Hz]	50/60Hz	50/60Hz
	Luminous Flux	[lm]	>1650	>2200
	Efficiency	[lm/W]	>110	>110
	CRI		>70	>70
	CCT	[K]	2700-7000K	2700-7000K
	LED Driver(brand)		RAYSHINE	RAYSHINE
	Output Voltage	[V]	24-42V	28-36V
	Output Current	[mA]	300mA±3%	300mA±3%
	Kind of LED		2 x COB	1 x COB
	Brand of LED Chip + Data Sheet		SAN'AN	SAN'AN
	Beam Angle		15°	100°
	Average Life	[h]	50000	50000
	Maintenance Luminous Flux 70%	[h]	50000	50000
	Ta - Working Ambient Temp.	[°C]	-40°C to +60°C	-40°C to +60°C
	Tc - Working Temperature	[°C]	90°C	90°C
	IP - Index Protection	IP	IP65	IP65
	Reflector Material		-	-
Difusor Material		PC	PC	
Body Material		stretching Alu.	stretching Alu.	
Weight	[Kg]	0.8kgs	0.8kgs	
Dimensions of Product (L x W x H)	[mm]	143*135*130 [mm]	143*135*130 [mm]	
Certificates (CE, Rohs, UL, . . .)		Rohs/CE	Rohs/CE	
Warranty by Supplier		3 Years	3 Years	
Inner	Kind of Packing		White box	White box
	Barcode		-	-
	Dimension (L x W x H)	[mm]	150*167*82 [mm]	150*167*82 [mm]
	Pcs/Ctn	Un/Cx	1.0kgs	1.0kgs
Outer	Kind of Packing		Export carton Packing	Export carton Packing
	Barcode		-	-
	Weight	[kg]	15.5kgs	15.5kgs
	Dimension (L x W x H)	[mm]	525*360*290mm	525*360*290mm
	Pcs/Ctn	Un/Cx	18pc/Ctn	18pc/Ctn

在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡。