

SINLOON®

聚光射燈/泛光燈

LED Floodlight

TSC series

Power:

50W

60W



■ Applications

It is suitable for using in parks, hotels, bars, gardens, buildings, lamp posts, playing grounds, stadiums.

■ Specification		Model:	TSC50CW-SD	TSC60W-SD
Technical Information	Wattage	[W]	50W	60W
	Input Voltage	[V]	AC90-265V	AC90-265V
	Input Current	[mA]	5500	6600
	Power Factor	[pf]	≥0.95	≥0.95
	Op. Frequency	[Hz]	50/60Hz	50/60Hz
	Luminous Flux	[lm]	>5500	>6600
	Efficiency	[lm/W]	>110	>110
	CRI	[Ra]	>70	>70
	CCT	[K]	2700-7000K	2700-7000K
	LED Driver(brand)	[Brand]	RAYSHINE	RAYSHINE
	Output Voltage	[V]	28-36V	28-36V
	Output Current	[mA]	1500mA±3%	1800mA±3%
	Kind of LED		1 x COB	1 x COB
	Brand of LED Chip + Data Sheet		SAN'AN	SAN'AN
	Beam Angle		30°/60°/120°	30°/60°/120°
	Average Life	[h]	50000	50000
	Maintenance Luminous Flux 70%	[h]	50000	50000
	Ta - Working Ambient Temp.	[°C]	-40°C to +60°C	-40°C to +60°C
	Tc - Working Temperature	[°C]	90°C	90°C
	IP - Index Protection	IP	IP65	IP65
Reflector Material		-	-	
Difusor Material		PC	PC	
Body Material		stretching Alu.	stretching Alu.	
Weight	[Kg]	1.4kgs	1.4kgs	
Dimensions of Product (L x W x H)	[mm]	230*135*135 [mm]	230*135*135 [mm]	
Certificates (CE, Rohs, UL, . . .)		Rohs/CE	Rohs/CE	
Warranty by Supplier		3 Years	3 Years	
Inner	Kind of Packing		White box	White box
	Bar code		-	-
	Dimension (L x W xH)	[mm]	240*167*87[mm]	240*167*87[mm]
	Pcs/Ctn	Un/Cx	1.5kgs	1.5kgs
Outer	Kind of Packing		Export carton Packing	Export carton Packing
	Barcode		-	-
	Weight	[kg]	17.5kgs	17.5kgs
	Dimension (L x W x H)	[mm]	525*390*290 [mm]	525*390*290 [mm]
	Pcs/Ctn	Un/Cx	12pc/Ctn	12pc/Ctn

在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡。